Application No.: Not Yet Assigned Docket No.: 0020-5368PUS1

AMENDMENTS TO THE CLAIMS

- 1. (Original) A polyester resin aqueous dispersion, comprising: a polyester resin (A) having an acid value of 2 mg KOH/g or more and less than 8 mg KOH/g and a number-average molecular weight of 5,000 or more; a basic compound (B); and water (C), wherein the content of the polyester resin (A) is 1 to 70 percent by mass, the content of water (C) is 10 percent by mass or more, and no surfactant is contained.
- 2. (Original) The polyester resin aqueous dispersion according to Claim 1, further comprising an organic solvent (D), wherein the content of the organic solvent (D) is 0 to 85 percent by mass.
- 3. (Original) The polyester resin aqueous dispersion according to claim 1 or 2, wherein the volume-average particle size of the particles in the polyester resin aqueous dispersion is 400 nm or less.
- 4. (Currently amended) The polyester resin aqueous dispersion according to any one of elaims 1 to 3 claim 1, wherein the polyester resin is a polyester resin having carboxyl groups introduced by using a polybasic acid in a depolymerization reaction and/or an addition reaction.
- 5. (Original) The polyester resin aqueous dispersion according to claim 4, wherein the polybasic acid is a trifunctional or higher polybasic acid.
- 6. (Currently amended) The polyester resin aqueous dispersion according to any one of claims 1 to 5 claim 1, wherein the polyester resin is a polyester resin containing an aromatic polybasic acid in an amount of 50 mole % or more as the polybasic acid component.
- 7. (Currently amended) A process for producing the polyester resin aqueous dispersion according to any one of claims 1 to 6 claim 1, comprising;

Application No.: Not Yet Assigned Docket No.: 0020-5368PUS1

dispersing a solution of a polyester resin (A) in an organic solvent together with a basic compound (B) in water by phase-inversion emulsification, wherein the phase-inversion emulsification is carried out at a temperature of 40°C or lower.

8. (Original) The process for producing the polyester resin aqueous dispersion according to Claim 7, further comprising;

removing the organic solvent after the phase-inversion emulsification.

9. (Original) The process for producing the polyester resin aqueous dispersion according to Claim 7 or 8, wherein the amount of the basic compound (B) used satisfies the following Formula (1):

$$-0.25 \times E + 2.5 \le F \le -5 \times E + 50 (1)$$

wherein in the formula (1) E represents an acid value of the polyester resin (A) (mg KOH/g); and F represents an equivalence ratio of the basic compound (B) to the total mole quantity of the carboxyl groups of polyester resin (A).